



Strip curtains

ANACONDA BELTING COMPANY

(A Division of Wildex Limited)

Unit 29 Church Road, Sittingbourne, Kent ME10 3RS

Tel: 01474 709784 Fax: 01474 709896

website: www.anacondabelting.co.uk

e-mail: sales@anacondabelting.co.uk



● This illustrates a 400mm x 4mm double overlap Clear P.V.C. Strip curtain.

Single Overlap 50%

Double Overlap 100%




FOR EXTERNAL OPENINGS WHERE CONTINUAL ACCESS OR LOADING OF VEHICLES IS UNDERTAKEN, ALSO FOR INTERNAL USE IN ORDER TO REGULATE TEMPERATURES.

Flexible strip curtains provide an easy and economical method of effectively sealing heat loss from an area where constant access to the outside is necessary. Clear P.V.C. strips, suspended from a mild steel section, are safe and easily replaced.

Curtains can be mounted on sliding door gear to slide clear of the opening.


Specification

High quality clear P.V.C. strips size 200mm x 2mm, 375mm x 2.5mm, 300mm x 3mm and 400mm x 4mm set with a single or double overlap and suspended from a 50mm x 50mm x 6mm mild steel angle section or a 65mm x 6mm mild steel flat bar section, according to requirements.




TYPE A

50mm x 50mm angle type top section for securing directly to the underside of the lintel.



TYPE B

65mm x 6mm flat bar type section for securing on to the face of the lintel.



TYPE C/TYPE D

Tubular Top Section with clip on swivel hinges. Soffit fixing (Type C) Face Fixing (Type D).

In order to specify your requirements the table gives details of the configurations available.

REF.	Suggested Maximum Opening Height	Overlap	Strip Width	Strip Thickness	Suitable for Interior Locations	Suitable for Exterior Locations
200S	Up to 2700mm (up to 9ft.)	50%	200mm	2mm	YES	NOT REC.
375S	Up to 3000mm (up to 10ft.)	40%	375mm	2.5mm	YES	NOT REC.
300S	Up to 3000mm (up to 10ft.)	50%	300mm	3mm	YES	NOT REC.
400S	Up to 4500mm (up to 15ft.)	50%	400mm	4mm	YES	Up to 3500mm (Up to 11'6")
200D	Up to 3600mm (up to 12ft.)	100%	200mm	2mm	YES	YES
375D	Up to 4000mm (up to 13ft.)	90%	375mm	2.5mm	YES	YES
300D	Up to 4000mm (up to 13ft.)	100%	300mm	3mm	YES	YES
400D	Up to 6000mm (up to 20ft.)	100%	400mm	4mm	YES	YES