



PINKL

PVC DUCTING
MEDIUM WEIGHT



CONSTRUCTION:

Double ply clear PVC ducting with a fully encapsulated PVC coated close pitch spring steel wire helix.

COLOUR:

Clear.

STANDARD LENGTH:

10 Metres.

TEMPERATURE RANGE:

0°C to +70°C in a 20°C ambient.

APPLICATIONS:

Ideal for low pressure, air, fume and dust handling.

PROPERTIES:

Lightweight easy to handle, smooth bore, durable with a high flex life.

OPTIONS:

P1.STD - Grey

Various colours

Technical Data

Diameter mm	Weight Kg/m	Bend Radius mm	Max. Work. Press. Bar	Max. Vacuum Bar
13	0.07	13	2.50	0.80
25	0.17	25	1.70	0.45
32	0.21	32	1.50	0.40
38	0.24	38	1.40	0.30
51	0.29	51	1.30	0.28
63	0.54	63	1.00	0.25
76	0.63	76	0.80	0.20
80	0.70	80	0.70	0.18
89	0.75	89	0.65	0.16
102	0.79	102	0.60	0.15
115	0.85	120	0.50	0.13
127	0.98	127	0.40	0.12
140	1.05	140	0.30	0.12
152	1.18	152	0.25	0.10
160	1.30	160	0.25	0.10
178	1.48	178	0.25	0.10
203	1.69	203	0.20	0.09
228	1.90	228	0.17	0.08
254	2.10	254	0.15	0.08
305	2.52	305	0.12	0.06
357	2.93	357	0.10	0.06
408	3.39	408	0.08	0.02

Technical data at + 20°C.

Other diameters/lengths available upon request.