




Data Sheet PVG150 Black S1CBB



A premium quality 100% Polyester carcass belt with the unique quiet weave low friction bottom cover, specially designed for use in applications where noise levels are a concern and reliable performance mandatory. Manufactured with a special PVG compound which is flame retardant to ISO340, static dissipative and has moderate oil resistance, The versatility of this belt makes it suitable for both flat and troughing applications.

Belt Construction

Number of fabrics	1	
Fabric material	Spun Polyester	
Top cover material	PVG	
Top cover thickness	1.3 mm	0.051 in
Top cover profile	Satin	
Top cover colour	Black	
Top cover hardness	70 Shore A	
Bottom cover material	Spun Polyester	
Bottom cover thickness	0.0 mm	0.000 in
Bottom cover profile	Quiet Weave Construction	

Technical Data

Thickness	3.7 mm	0.146 in
Weight	4.60 kg/m ²	0.943 lbs/ft ²
Tensile strength for 1% elongation	26 n/mm	145.33 lbs/in
Minimum pulley diameter	64 mm	0.236 in
Minimum pulley back flex diameter	70 mm	2.756 in
Minimum temperature	-7 °C	19.4 °F
Maximum temperature	80 °C	176 °F
Maximum width	2000 mm	78.740 in

Characteristics

Slider Bed	Yes
Carry Rollers	Yes
Troughed	Yes
Food Quality	Yes
Oil and Fat Resistant	Yes
Flame Retardant	Yes
Anti Static	Yes

Due to our continuous search for improvement, the above data is subject to alteration. This data replaces any previous publications. Anaconda belting excludes any liability for the incorrect use of the above stated information. All activities performed and services rendered by Anaconda Belting are subject to the general terms and conditions of sale.