



TYPE SJ STARCO JUMBO™

Developed to meet the needs of industrial elevators, particularly cement. Deep drawn solid steel bucket, designed and engineered to replace large fabricated buckets. Suitable for use with both standard rubber and steel cord belting.

- > **Improved capacity:** Wingless design, improves fill and allows closer spacing
- > **Greater strength/longer life:** Solid seamless construction with rounded corners for rigidity. No welds or joints to open up
- > **Economic solution**
- > **More buckets per metre:** More capacity, smaller casing

PRESSED SEAMLESS STEEL

Industrial



No.	A (mm)	B (mm)	C (mm)	D (mm)	T (mm)	(kg)	Capacity (Litres)		Recessed Holes				Max. Pcs/Mtr
							Z2 (total)	Z3 (water)	No.	E (Ø mm)	F (mm)	G (mm)	
SJ330-250/3	340	260	190	130	3.0	4.5	9.6	7.2	3	13	80	55	5
SJ330-250/4	340	260	190	130	4.0	6.0	9.6	7.2	3	13	80	55	5
SJ370-250/3	380	260	190	130	3.0	5.1	10.8	8.3	4	13	80	55	5
SJ370-250/4	380	260	190	130	4.0	6.8	10.8	8.3	4	13	80	55	5
SJ470-250/3	480	260	190	130	3.0	6.5	14.0	10.5	5	13	80	55	5
SJ470-250/4	480	260	190	130	4.0	8.6	14.0	10.5	5	13	80	55	5

Special holes/thicknesses/wearbands - available on request

Free Engineering Design Service - contact Anaconda Belting Company

